

Product Specifications - Hi Performance Window Film

	Visible Light		Solar Energy							
	VLT	VLR	TST	TSR	TSA	UVT	IRR	UVALUE	PLY	Thickness
ST - Black 20% Reflective 2 Ply	14%	3%	33.5%	11.3%	55.2%	<1%	48%	1.12	2Ply	2mil
ST - Black 35% Reflective 2 Ply	22%	5%	37.2%	12.1%	50.7%	<1%	49%	1.12	2Ply	2mil
Nano Ceramic 80& - Charcoal 20%	20%	3%	55.3%	8.3%	36.4%	<2%	13%	0.98	2Ply	1.5mil
Nano Ceramic 80% - Charcoal 35%	33%	7%	62.1%	9.5%	28.4%	<2%	12%	0.98	2Ply	1.5mil
Nano Ceramic SL - 7085	72.7%	11.2%	37.7%	11.9%	50.4%	<1.1%	88%	0.89	2Ply	1.5mil
Stainless Steel Sputter 16%	41%	26.4%	22.4%	24%	53.6%	5%	79%	1.03	2Ply	2mil
ST Black 20% Non Reflective	20%	3%	53.3%	8.3%	36.4%	<2%	13%	1.12	2Ply	1.5mil
ST Black 35% Non Reflective	33%	7%	62.1%	9.5%	28.4%	<2%	12%	1.12	2Ply	1.5mil
Silver 15% Exterior	32%	45%	10%	49%	41%	<1%	68%	1.01	2Ply	1.5mil

🏠 104 Anton Lembede Street, Durban, 4001, South Africa 📮 P.O.Box 10394, Marine Parade, 4056

☎ + 27 31 332 4735 📠 + 27 31 332 3287 👤 0861 001 084 ✉ info@sff.co.za 🌐 www.sff.co.za