



SolarFilmFoundation

window film | graphics | design

Product Specifications - Reflective Window Film

	Visible Light		Solar Energy							
	VLT	VLR	TST	TSR	TSA	UVT	IRR	UVALUE	PLY	Thickness
Blue Reflective	20%	25%	11%	35%	54%	5%	80%	0.91	2 Ply	1.5 mil
Grey Reflective	11%	13%	10%	37%	53%	5%	77%	0.91	2 Ply	1.5 mil
Bronze Reflective	13%	19%	10%	38%	52%	5%	80%	0.91	2 Ply	1.5 mil
Gold Reflective	15%	52%	16%	33%	51%	5%	73%	0.91	2 Ply	1.5 mil
Silver Reflective 05%	4.8%	82.3%	4.23%	77.49%	18.23%	<1%	95%	0.98	2 Ply	1.5 mil
Silver Reflective 15%	17%	56%	10%	49%	41%	<1%	81%	1.01	2 Ply	1.5 mil
Silver Reflective 30%	28%	48.3%	24.11%	48.18%	27.71%	<1%	77%	1.02	2 Ply	1.5 mil
Silver Reflective 45%	43%	36.5%	32.2%	36.86%	30.94%	<1%	70%	1.03	2 Ply	1.5 mil
Silver Reflective 50&	48.5%	26.6%	38.9%	29.2%	31.9%	<1%	64%	1.04	2 Ply	1.5 mil
Grey 11% Reflective 2 Ply	13%	14%	11%	26%	63%	5%	85%	1.03	2 Ply	1.5 mil
Grey 28% Reflective 2 Ply	24%	9%	46%	16%	38%	5%	72%	1.05	2 Ply	1.5 mil
Charcoal 20% Metalized 2 Ply	16.7%	9.5%	49.3%	15%	35.7%	<1%	42.1%	1.11	2 Ply	1.5 mil
Charcoal 35% Metalized 2 Ply	32%	9.8%	45.5%	16%	45.4%	<1%	43%	1.12	2 Ply	1.5 mil
Charcoal 50% Metalized 2 Ply	44%	9.5%	49.3%	15%	35.7%	<1%	42.1%	1.12	2 Ply	1.5 mil
Charcoal 70% Metalized 2 Ply	63%	9.1%	56.2%	14.5%	29.3%	<1%	44%	1.14	2 Ply	1.5 mil

🏠 104 Anton Lembede Street, Durban, 4001, South Africa 📮 P.O.Box 10394, Marine Parade, 4056

☎ + 27 31 332 4735 📠 + 27 31 332 3287 👤 0861 001 084 ✉ info@sff.co.za 🌐 www.sff.co.za