

## Product Specifications - Safety &amp; Security Window Film

	Visible Light		Solar Energy							
	VLT	VLR	TST	TSR	TSA	UVT	IRR	UVALUE	PLY	Thickness
Black 20% 100 Micron Safety	19%	7%	63%	6%	31%	<2%	12%	1.12	2 Ply	4 mil
Black 35% 100 Micron Safety	33%	7%	67%	6%	27%	<2%	11%	1.12	2 Ply	4 mil
Black 50% 100 Micron Safety	49%	7%	63%	6%	31%	<2%	12%	1.14	2 Ply	4 mil
Charcoal 20% 125 Micron Metalized	16.7%	9.3%	37.3%	17.3%	45.4%	<1%	45%	0.98	2 Ply	5 mil
Charcoal 35% 125 Micron Metalized	32%	9.5%	45.5%	15%	38.5%	<1%	42.1%	0.98	2 Ply	5 mil
Charcoal 50% 125 Micron Metalized	44%	9.5%	49.3%	15%	35.7%	<1%	42.1%	0.99	2 Ply	5 mil
Clear Safety 50 Micron	91%	12%	77%	5%	18%	5%	8%	1.07	2 Ply	2 mil
Clear Safety 100 Micron	91%	7%	76%	11%	13%	5%	10%	1.07	2 Ply	4 mil
Clear Safety 175 Micron	86%	7%	68%	19%	13%	5%	12%	1.06	2 Ply	7 mil
Silver 15% 100 Micron Safety	14.2%	68.9%	66.6%	11%	22.4%	<1%	89%	0.98	2 Ply	4 mil

🏠 104 Anton Lembede Street, Durban, 4001, South Africa 📮 P.O.Box 10394, Marine Parade, 4056

☎ + 27 31 332 4735 📠 + 27 31 332 3287 👤 0861 001 084 ✉ info@sff.co.za 🌐 www.sff.co.za